

Solvent resistant suction and discharge hose, food grade, anti-static

Product images	Application	Characteristic	Structure
	► Chemical solvent suction and discharge	► High voltage resistance 16bar	► Color: Outer layer blue
	► High pressure cleaning equipment	► Smooth surface/inner wall	Inner layer off white
	► liquid delivery	► Ozone resistant and aging resistant	► Temperature: -30/+90°C
	► Food industry	► Resistant to 98% chemicals	► safety factor: 3:1
► Inner layer of pipe: UHMWPE	► Chemical factory	► Acid and alkali resistant	
► Reinforcement: Double layer high-strength fiber thread	► Conductive site	► Anti static with copper wire	
Spiral steel wire+conductive copper wire		► Compliant with the US FDA Food Contact Material Standards	
► Outer layer of tube: EPDM			

Part Number	Internal diameter mm	Outer diameter mm	Weight kg/m	Bending radius mm	Working pressure bar	Vacuum bar	Coil length m
201P-006-30	6.35	15	0.25	69	16	0.95	30
201P-013-30	12.70	20	0.41	127	16	0.95	30
201P-019-30	19	31	0.6	188	16	0.95	30
201P-025-30	25	37	0.73	225	16	0.95	30
201P-032-30	32	44	0.88	263	16	0.95	30
201P-038-30	38	51	1.01	338	16	0.95	30
201P-051-30	51	66	1.78	413	16	0.95	30
201P-063-30	63	79	2.39	450	16	0.95	30
201P-076-30	76.2	92	2.81	525	16	0.95	30
201P-102-30	101.6	118	3.87	675	16	0.95	30

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.

* We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.